



2542 TREE SAP REMOVER

PRODUCT INFORMATION SHEET

BE GREAT! BE DISTINCTIVE!

Using the **TREE SAP REMOVER** sap and other droppings from trees, birds, and bugs can be eliminated from painted surfaces along with plastic, rubber and glass. It also can be used on painted plastic and moldings. **TREE SAP REMOVER** works on both old/cured and newly deposited sap.

• **Features:**

- Proprietary blend of solvents and surfactants
- User friendly formulation
- Ready-to use

▪ **Benefits:**

- Lifts and suspends sap for easy removal
- Safe on clear coats
- No mixing necessary

• **Use for:**

- Old and new tree sap
- Bug and bird dropping removal
- Tar and grease removal

▪ **How to use:**

- Consult SDS for complete safety information before using.
- Do not apply to a hot surface or let dry on surface.
- Do not apply to freshly painted surfaces
- Spray Tree Sap Remover on the affected area, keeping the area wet with the remover.
- Using a cloth, plastic razor blade or sponge soaked with the remover, gently rub the sap to soften and remove from the surface.
- Wipe dry with a clean towel.
- Repeat as necessary.

▪ **Tech Tip:**

- Use **TREE SAP REMOVER** to remove wax and glaze residue on moldings.



Order by these numbers:

- | | | |
|------------------------------|------------------------|--|
| 25423 quart | 25424 gallon | 25425 5 gallon pail |
| 2542S 5 gallon square | 25426 30 gallon | 25427 55 gallon |
| | | 2542P Product Information Sheet |