

CLAY BAR LUBRICANT 4002

For clay applications

body shop safe

Description: **CLAY BAR LUBRICANT** creates a barrier between the paint and the clay cleaning material. The high lubricity of our **CLAY BAR LUBRICANT** prevents loosened contamination from scratching delicate clear coat finishes yet it will not break down or degrade the integrity of the clay. Our **CLAY BAR LUBRICANT** is safe for all body shop applications.

§ **Features:**

- Proprietary blend of surfactants
- No silicones harmful to paint
- Ready-to use

§ **Benefits:**

- Creates a micro barrier between clay and paint
- Body shop safe
- No mixing necessary

§ **Use for:**

- Lubricating ordinary clay bars
- Removing smudges from window glass
- Removing clay residue from cleaned and clayed surfaces

§ **How to use:**

- Consult MSDS for complete safety information before using.
- Mist a small area (2 sq. ft.) of the vehicle
- Rub clay cleaning material over the surface.
- Continue lightly rubbing the clay over the surface until it moves freely.
- When the bar moves freely, the surface is clean.
- Wipe off any residues and proceed to the next area.

§ **Tech Tip:**

- Keep the surface saturated throughout the process, and knead the clay periodically to ensure the bar's surface is clean.



BE GREAT BE DISTINCTIVE !™

distinctivedetailsinc.com

DISTINCTIVE DETAILS INC.

P.O. Box 59422 Pittsburgh, PA 15210

1-800-243-5389

• **Order by these numbers:**

- | | |
|---------------------------------|-----------------------|
| 40023 quart | 40024 gallon |
| 40025 5 gallon pail | 4002S 5 gallon square |
| 40026 30 gallon | 40027 55 gallon drum |
| 4002P Product Information Sheet | |

ac Reorder 4002P