



2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 8/5/2025

Revision date: 8/5/2025

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 2037 Brake Dust Eliminator
Product code : 2037

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Removes brake dust and dirt from wheels

1.3. Manufacturer

Manufacturer

Distinctive Details Inc.
1253 Lower Elkton Rd.
Columbiana, OH 44408
T 1 800-711-7021
www.DistinctiveDetailsInc.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (Chemtrec 24 Hr. Emergency Line)
International: +1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Skin Corr. 1A
Eye Dam. 1
Carc. 2
STOT RE 1
HHNOC 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS)



Signal word (GHS)

: Danger

Hazard statements (GHS)

: Causes severe skin burns and eye damage.
Suspected of causing cancer.
Causes damage to organs through prolonged or repeated exposure.
Causes severe damage to the respiratory tract

Precautionary statements (GHS)

: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust, fume, gas, mist, spray, vapours.
Wash face, hands thoroughly after handling.
Do not eat, drink or smoke when using this product

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Wear eye protection, face protection, protective gloves, protective clothing.
If exposed or concerned: Get medical advice/attention
If swallowed: rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Get medical advice/attention if you feel unwell.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Coconut diethanolamide	Coconut diethanolamide Alkanolamide of coconut oil fatty acids and diethanolamine / Amides, coco, N,N-bis(2-hydroxyethyl) / Amides, coco, N,N-bis(hydroxyethyl) / N,N-Bis(2-hydroxyethyl)cocoamide / N,N-Bis(2-hydroxyethyl)coconut oil amide / Coconut acid, diethanolamide / Coconut oil acid diethanolamide condensate / Coconut oil acids, diethanolamine condensate / Coconut oil diethanolamide / Coconut oil fatty acid diethanolamide / Coconut oil fatty acids, diethanolamide / Coconut oil, diethanolamide / Cocamide DEA / Coconut oil acid diethanolamine condensate / Coconut fatty acid diethanolamide / COCAMIDE DEA / Coconut oil acid diethanolamide / Palm kernel diethanolamide / Coconut oil diethanolamine condensate / Cocamide diethanolamine / N,N-Bis(hydroxyethyl) coco amides / N,N-Bis(2-hydroxyethyl)cocoalkylamide / N,N-Bis(hydroxyethyl)(coco amides)	CAS-No.: 68603-42-9	10 - 30
Potassium hydroxide	Potassium hydroxide Caustic potash / Potassium hydroxide (K(OH)) / POTASSIUM HYDROXIDE	CAS-No.: 1310-58-3	3 - 10

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy-, mono-C8-10-alkyl ethers, phosphates	Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy-, mono-C8-10-alkyl ethers, phosphates C8-10-Alkyl alcohol ethoxylate, phosphate ester / Polyethyleneglycol monoalkyl (C8-10) ether phosphate / Polyethylene glycol mono alkyl (C8-10) ether phosphate / .alpha.-Hydroxy-.omega.-hydroxypoly(oxy-1,2-ethanediyl)alkyl (C8-10) ethers phosphate	CAS-No.: 68130-47-2	1 - 5
2-butoxyethanol	2-butoxyethanol 2-Butoxy-1-ethanol / Butoxyethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether / Ethylene glycol n-butyl ether / Hydroxyethyl butyl ether / Ethylene glycol butyl ether / 2-Butoxyethan-1-ol / Ethylene glycol mono-n-butyl ether / 2-n-Butoxyethanol / Butyl glycol / BUTOXYETHANOL / EGBE / EGMBE / Butoxyethanol, 2- / Butyl Cellosolve / Monobutyl ether of ethyleneglycol	CAS-No.: 111-76-2	1 - 5
Sodium xylenesulfonate	Sodium xylenesulfonate Sodium xylene sulfonate / Benzenesulfonic acid, dimethyl-, sodium salt / Sodium dimethylbenzenesulfonate / Sodium xylenesulphonate / Xylenesulfonate, sodium / Xylenesulfonic acid, sodium salt / Benzenesulphonic acid, dimethyl-, sodium salt / Benzenesulfonic acid, dimethyl-, sodium salt (1:1) / SODIUM XYLENESULFONATE / Dimethylbenzenesulfonic acid, sodium salt	CAS-No.: 1300-72-7	1 - 5
Diethanolamine	Diethanolamine Bis(2-hydroxyethyl)amine / DEA / Di(2-hydroxyethyl)amine / 2,2'-Dihydroxydiethylamine / Ethanol, 2,2'-iminobis- / Ethanol, 2,2'-iminodi- / 2-(2-Hydroxyethylamino)ethanol / 2,2'-Iminodiethanol / Diolamine / N,N-Diethanolamine	CAS-No.: 111-42-2	0.5 - 1.5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor.
First-aid measures after skin contact	: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Causes severe damage to the respiratory tract. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Chronic symptoms : Suspected of causing cancer.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water. Dry powder. Carbon dioxide. Foam.
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Nitrogen oxides. Toxic and corrosive vapours may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

Emergency procedures : Do not touch or walk on the spilled product. Evacuate unnecessary personnel.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapors/ spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Provide adequate ventilation.
Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep only in original container. Store locked up. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2037 Brake Dust Eliminator	
No additional information available	
Potassium hydroxide (1310-58-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL C	2 mg/m ³
2-butoxyethanol (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
BEI	200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL TWA [1]	240 mg/m ³
OSHA PEL TWA [2]	50 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Coconut diethanolamide (68603-42-9)	
No additional information available	
Diethanolamine (111-42-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ (inhalable fraction and vapor)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, Skin - potential significant contribution to overall exposure by the cutaneous route

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-hydroxy-, mono-C8-10-alkyl ethers, phosphates (68130-47-2)

No additional information available

Sodium xylenesulfonate (1300-72-7)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : No data available

Odour : No data available

Odour threshold : No data available

pH : 13.96

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Relative evaporation rate (butylacetate=1) : No data available

Flammability : Not flammable.

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

Relative density : No data available

Solubility : No data available

Partition coefficient n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive limits : No data available

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Explosive properties : No data available
Oxidising properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agent. Strong acids.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Nitrogen oxides. Toxic and corrosive vapours may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

2037 Brake Dust Eliminator

Potassium hydroxide (1310-58-3)

LD50 oral rat	284 mg/kg
ATE CA (oral)	284 mg/kg bodyweight

2-butoxyethanol (111-76-2)

LD50 oral rat	1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301
LD50 dermal rabbit	435 mg/kg
LC50 inhalation rat	2.35 mg/l
LC50 inhalation rat	486 ppm/4h
ATE CA (oral)	1414 mg/kg bodyweight
ATE CA (Dermal)	435 mg/kg bodyweight

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2-butoxyethanol (111-76-2)	
ATE CA (Gases (except aerosol dispensers and lighters))	486 ppmv/4h
ATE CA (vapours)	2.35 mg/l/4h
ATE CA (dust,mist)	2.35 mg/l/4h
Coconut diethanolamide (68603-42-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2 g/kg
Diethanolamine (111-42-2)	
LD50 oral rat	780 mg/kg
LD50 dermal rabbit	11.9 ml/kg
ATE CA (oral)	780 mg/kg bodyweight
ATE CA (Dermal)	13034.07 mg/kg bodyweight
Sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	≥ 3346 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), 95% CL: 3196 - 3503
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes severe skin burns. pH: 13.96
Serious eye damage/irritation	: Causes serious eye damage. pH: 13.96
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.
2-butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable
Coconut diethanolamide (68603-42-9)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
Diethanolamine (111-42-2)	
NOAEL (chronic, oral, animal/male, 2 years)	64 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Remarks on results: other:
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
Sodium xylenesulfonate (1300-72-7)	
NOAEL (chronic, oral, animal/female, 2 years)	≥ 60 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Remarks on results: other:
Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2-butoxyethanol (111-76-2)	
STOT-single exposure	May cause respiratory irritation.

: Causes damage to organs through prolonged or repeated exposure.

STOT-repeated exposure

2-butoxyethanol (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Diethanolamine (111-42-2)	
LOAEL (dermal, rat/rabbit, 90 days)	32 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.003 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Sodium xylenesulfonate (1300-72-7)	
NOAEL (oral, rat, 90 days)	763 – 3534 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: Causes severe damage to the respiratory tract. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic symptoms	: Suspected of causing cancer.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

2-butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'

Coconut diethanolamide (68603-42-9)	
LC50 - Fish [1]	3.6 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])

Diethanolamine (111-42-2)	
LC50 - Fish [1]	460 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	30.1 mg/l Test organisms (species): Ceriodaphnia dubia

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Diethanolamine (111-42-2)	
LC50 - Fish [2]	1200 – 1580 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [2]	89.9 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 - Other aquatic organisms [2]	2.1 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
ErC50 algae	2.1 mg/l
LOEC (chronic)	1.56 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.78 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1 mg/l Test organisms (species): other:
NOEC chronic crustacea	0.78 mg/l
Sodium xylenesulfonate (1300-72-7)	
LC50 - Fish [1]	≥ 1580 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1020 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

2037 Brake Dust Eliminator	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

2037 Brake Dust Eliminator	
Bioaccumulative potential	Not established.
Potassium hydroxide (1310-58-3)	
Partition coefficient n-octanol/water	0.65
2-butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water	0.81 (at 25 °C)
Diethanolamine (111-42-2)	
BCF - Fish [1]	(no significant bioconcentration)
Partition coefficient n-octanol/water	-2.18 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional information : Empty containers may contain residues which are hazardous.

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

DOT NA No : UN1760
UN-No. (TDG) : UN1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. (Potassium hydroxide)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : 8
Hazard labels (TDG) : 8



14.4. Packing group

Packing group (DOT) : I
Packing group (TDG) : I

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

UN-No.(DOT) : UN1760

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

DOT Special Provisions (49 CFR 172.102)	: A7 - Steel packagings must be corrosion-resistant or have protection against corrosion. B10 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks, and DOT 57 portable tanks are not authorized. T14 - 6 6 mm Prohibited 178.275(g)(3). TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 201
DOT Packaging Bulk (49 CFR 173.xxx)	: 243
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 0.5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 2.5 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
TDG	
UN-No. (TDG)	: UN1760
TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.
ERAP Index	: 3000
Explosive Limit and Limited Quantity Index	: 0
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 0.5 L
Emergency Response Guide (ERG) Number	: 154

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

2037 Brake Dust Eliminator

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date : 08/05/2025
Revision date : 08/05/2025
Other information : None.


Full text of H-statements

Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
HHNOC 1	Health hazard not otherwise classified, category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

2037 BRAKE DUST ELIMINATOR



Danger

Causes severe skin burns and eye damage. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. Causes severe damage to the respiratory tract.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume, gas, mist, spray, vapours. Wash face, hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, face protection, protective gloves, protective clothing. If exposed or concerned: Get medical advice/attention. If swallowed: rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Get medical advice/attention if you feel unwell. Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.



WARNING:

This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Distinctive Details Inc.

1253 Lower Elkton Rd.

Columbiana, OH 44408

1 800-711-7021

www.DistinctiveDetailsInc.com

