



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 2502 Body Solv

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Manufacturer

Company

Address

: Distinctive Details, Inc.
1253 Lower Elkton Road
Columbiana OH 44408
United States of America

Emergency telephone number:

CHEMTREC 800.424.9300

Additional Information:

SDS Requests: 1-800-711-7021
Website: www.DistinctiveDetailsInc.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity
(Inhalation) : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system, Peripheral nervous system)

Specific target organ toxicity - repeated exposure
(Inhalation) : Category 2 (Auditory system, Eyes)

Aspiration hazard : Category 1

Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

GHS Label element

Hazard pictograms



Signal word

: Danger

Hazard statements

: H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs (Central nervous system, Peripheral nervous system) through prolonged or repeated exposure.
H373 May cause damage to organs (Auditory system, Eyes) through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Emergency Overview

Appearance	liquid
Colour	Clear, Colorless



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Odour	Characteristic
Hazard Summary	No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Concentration (%)
68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hy- drotreated lt AND/OR Solvent naphtha (pet), lt aliph.	50 - 70
108-88-3	Toluene	30 - 50
111-65-9	**Octane	1 - 5
142-82-5	**Heptane	1 - 5

Special Notes: : ** Other substances in the product which may present a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
--------------	--

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Use a water spray to cool fully closed containers.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for fire-fighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
---	---



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of	Control parameters / Permissi-	Basis
---------	------------	------------------------	--------------------------------	-------



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

		exposure)	ble concentra- tion	
68410-97-9 / 64742-49- 0 / 64742- 89-8	Distillates, pet, It dist hy- drotreat process, low-boil AND/OR Naphtha (pet), hydrotreated It AND/OR Solvent naphtha (pet), It aliph.	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
108-88-3	Toluene	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
111-65-9	**Octane	TWA	300 ppm	ACGIH
		TWA	75 ppm 350 mg/m3	NIOSH REL
		C	385 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,350 mg/m3	OSHA Z-1
		TWA	300 ppm 1,450 mg/m3	OSHA P0
		STEL	375 ppm 1,800 mg/m3	OSHA P0
142-82-5	**Heptane	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
When using do not eat or drink.



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

When using do not smoke.
Wash hands before breaks and immediately after
handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: Clear, Colorless
Odour	: Characteristic
Odour Threshold	: No data available
pH	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash point	: 7 °C (45 °F)
Evaporation rate	: 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Burning rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: > 1(Air = 1.0)
Relative density	: 0.782 @ 25 °C (77 °F) Reference substance: (water = 1)
Density	: 0.782 g/cm ³ @ 25 °C (77 °F)
Bulk density	: No data available
Water solubility	: No data available
Solubility in other sol- vents	: No data available



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Thermal decomposition : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No hazards to be specially mentioned.

Conditions to avoid : Extremes of temperature and direct sunlight.
Keep away from heat, flame, sparks and other ignition sources.

Incompatible materials : Strong oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 4.51 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: The substance or mixture has no acute



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

oral toxicity

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

108-88-3:

Acute oral toxicity : LD50 (Rat, male): > 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 28.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Species: Rabbit
Exposure time: 4 h
Result: Irritating to skin.

108-88-3:

Species: Rabbit
Exposure time: 4 h
Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Species: Rabbit
Result: Irritating to eyes.

108-88-3:

Species: Rabbit
Result: Irritating to eyes.
Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Components:



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

68410-97-9 / 64742-49-0 / 64742-89-8:

Test Type: Buehler Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

108-88-3:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

GLP: yes

Germ cell mutagenicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Germ cell mutagenicity-
Assessment : Mutagenicity classification not possible from current data

108-88-3:

Genotoxicity in vitro : Test Type: Mammalian cell gene mutation assay
Test species: Mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Dominant lethal assay
Test species: Mouse (male)
Application Route: inhalation (vapour)
Exposure time: 6 h/d, 5 d/wk for 8 wks
Dose: 0, 100, 400 ppm
Method: OECD Test Guideline 478
Result: negative

Germ cell mutagenicity-
Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

108-88-3:

Species: Rat, (male and female)

Application Route: inhalation (vapour)

Exposure time: 103 wks

Dose: 0, 600, 1200 ppm

Frequency of Treatment: 6.5 h/d, 5 d/wk



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

NOAEL: No observed adverse effect level: 1,200 ppm

Method: OECD Test Guideline 453

Result: did not display carcinogenic properties

Symptoms: Erosion of nasal epithelium

GLP: yes

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Reproductive toxicity - Assessment : Fertility classification not possible from current data.
Embryotoxicity classification not possible from current data.

108-88-3:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Inhalation
Dose: 0, 100, 500, 2000 ppm
Frequency of Treatment: 7 days/week
General Toxicity - Parent: NOAEC: 500 ppm
General Toxicity F1: NOAEC: 500 ppm
Fertility: NOAEC: 2,000 ppm
Symptoms: Reduced maternal body weight gain Reduced offspring weight gain
Method: OECD Test Guideline 416
Result: Animal testing did not show any effects on fertility.
GLP: yes

Test Type: Fertility
Species: Rat, male and female
Application Route: inhalation (vapour)
Dose: 0, 600, 1200 ppm
Frequency of Treatment: 7 days/week
General Toxicity - Parent: NOAEC: 600 ppm
Symptoms: Decreased sperm count
Result: Animal testing did not show any effects on fertility.

Effects on foetal development : Species: Rat
Application Route: inhalation (vapour)
Dose: 0, 250, 750, 1500, 3000 ppm
Duration of Single Treatment: 10 d
Frequency of Treatment: 6 hr/day
General Toxicity Maternal: NOAEC: 750 ppm



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Developmental Toxicity: NOAEC: 750 ppm
Symptoms: Maternal toxicity, Reduced body weight,
Skeletal malformations
GLP: yes

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

Product: No data available

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Central nervous system	May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.	

108-88-3:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Central nervous system	May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.	

111-65-9: No data available

142-82-5: No data available

STOT - repeated exposure

Product: No data available

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Exposure routes:	Target Organs:	Assessment:	Remarks:
------------------	----------------	-------------	----------



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

	Central nervous system, Peripheral nervous system	The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.	
--	---	--	--

108-88-3:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Auditory system, Eyes	May cause damage to organs through prolonged or repeated exposure., The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.	

111-65-9:No data available

142-82-5:No data available

Repeated dose toxicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Species: Rat, male and female

NOAEL: 1402

Application Route: inhalation (vapour)

Test atmosphere: vapour

Exposure time: 13

Number of exposures: 6 hours/day, 5 day

Dose: 322,1402, 9869 mg/m³

GLP: yes

Target Organs: Kidney

Symptoms: Nasal and ocular discharge

108-88-3:

Species: Rat, male and female

NOAEL: 300

Application Route: inhalation (vapour)

Exposure time: 6, 12, or 18 mths



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Number of exposures: 6 h/d, 5 d/wk
Dose: 0, 30, 100, 300 ppm
Method: OECD Test Guideline 453

Repeated dose toxicity - : Causes skin irritation.
Assessment

Aspiration toxicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

May be fatal if swallowed and enters airways.

108-88-3:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l
Exposure time: 96 h
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test Type: Immobilization
Analytical monitoring: yes



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7
Exposure time: 96 h
Test Type: static test

Ecotoxicology Assessment
Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

108-88-3:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia): 3.78 mg/l
Exposure time: 48 h
Test Type: Renewal

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 134 mg/l
Exposure time: 3 h
Test Type: static test

Toxicity to bacteria : IC50 (Bacteria): 84 mg/l
Exposure time: 24 h
Test Type: Static

Ecotoxicology Assessment
Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Biodegradability : Concentration: 49.2 mg/l
Result: Readily biodegradable
Biodegradation: 77 %
Testing period: 2 d
Exposure time: 28 d

108-88-3:

Biodegradability : Inoculum: Sewage
Biodegradation: 100 %
Remarks: Readily biodegradable



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Bioaccumulative potential

Components:

108-88-3:

Partition coefficient: n-octanol/water : log Pow: 2.73

111-65-9:

Partition coefficient: n-octanol/water : log Pow: 5.15

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

Components:

68410-97-9 / 64742-49-0 / 64742-89-8:

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

IATA (International Air Transport Association): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, Flash Point: 7 °C (45 °F)

IMDG (International Maritime Dangerous Goods): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, Marine Pollutant (DISTILLATES (PETROLEUM), LIGHT DISTILLATE HYDROTREATING PROCESS, LOW-BOILING, TOLUENE)

DOT (Department of Transportation): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

SECTION 15. REGULATORY INFORMATION

OSHA Hazards : Flammable liquid, Moderate skin irritant, Moderate eye irritant, Teratogen, Reproductive hazard, Toxic by inhalation, Specific target organ toxicity - single exposure, Specific target organ toxicity - repeated exposure, Aspiration hazard

WHMIS Classification : B2: Flammable liquid
D2A: Very Toxic Material Causing Other Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	2981

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Immediate (Acute) Health Hazard
Chronic (Delayed) Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

108-88-3	Toluene	33.5456 %
----------	---------	-----------

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

108-88-3	Toluene	33.5456 %
----------	---------	-----------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMII Intermediate or Final VOC's (40 CFR 60.489):

108-88-3	Toluene	33.5456 %
----------	---------	-----------

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	Toluene	33.5456 %
100-41-4	**Ethylbenzene	0.0998 %
71-43-2	Benzene	0.04 %
91-20-3	**Naphthalene	0.0066 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	Toluene	33.5456 %
100-41-4	**Ethylbenzene	0.0998 %
71-43-2	Benzene	0.04 %
91-20-3	**Naphthalene	0.0066 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

108-88-3	Toluene	33.5456 %
----------	---------	-----------

US State Regulations

Massachusetts Right To Know

108-88-3	Toluene	30 - 50 %
111-65-9	**Octane	1 - 5 %
142-82-5	**Heptane	1 - 5 %
71-43-2	Benzene	0 - 0.1 %

Pennsylvania Right To Know

68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated lt AND/OR Solvent naphtha (pet), lt aliph.	50 - 70 %
108-88-3	Toluene	30 - 50 %
111-65-9	**Octane	1 - 5 %
142-82-5	**Heptane	1 - 5 %
100-41-4	**Ethylbenzene	0 - 0.1 %



Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

71-43-2 Benzene 0 - 0.1 %

New Jersey Right To Know

68410-97-9 / Distillates, pet, lt dist hydrotreat 50 - 70 %
64742-49-0 / process, low-boil AND/OR Naphtha
64742-89-8 (pet), hydrotreated lt AND/OR Solvent
naphtha (pet), lt aliph.
108-88-3 Toluene 30 - 50 %
111-65-9 **Octane 1 - 5 %
142-82-5 **Heptane 1 - 5 %

California Prop 65

100-41-4 **Ethylbenzene
71-43-2 Benzene
91-20-3 **Naphthalene
98-82-8 Cumene
WARNING! This product contains a chemical known to the State of California to cause cancer.
108-88-3 Toluene
71-43-2 Benzene
WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

The components of this product are reported in the following inventories:

United States TSCA Inventory	:	y (positive listing) (On TSCA Inventory)
Canadian Domestic Substances List (DSL)	:	y (positive listing) (All components of this product are on the Canadian DSL.)
Australia Inventory of Chemical Substances (AICS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
New Zealand. Inventory of Chemical Substances	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Japan. ENCS - Existing and New Chemical Substances Inventory	:	n (Negative listing) (Not in compliance with the inventory)
Korea. Korean Existing Chemicals Inventory (KECI)	:	y (positive listing) (On the inventory,



Safety Data Sheet

2507 - Adhesive Label Remover


Version 0.0

Revision Date: 09/01/2025

		or in compliance with the inventory)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
China. Inventory of Existing Chemical Substances in China (IECSC)	:	y (positive listing) (On the inventory, or in compliance with the inventory)

SECTION 16. OTHER INFORMATION **Further information**

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Legacy SDS: R0014154

Material number:
16027965, 16027964, 784226, 542268, 103152

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Gov-	LD50	Lethal Dose 50%

Safety Data Sheet

2507 - Adhesive Label Remover

Version 0.0

Revision Date: 09/01/2025

	ernment Industrial Hygienists		
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%