

Version 1.1

Revision Date: 06/01/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION Product name : Solv-All Recommended use of the chemical and restrictions on use Recommended use : Industrial chemical Manufacturer or supplier's details Company : Distinctive Details, Inc. 1253 Lower Elkton Road Columbiana, OH 44408 United States of America (USA) Emergency telephone number: Transport North America: CHEMTREC (1-800-424-9300)

CHEMTREC INTERNATIONAL Tel # 703-527-3887

Additional Information:	:	Responsible Party: Product Compliance Department
		SDS Requests: 1-800-711-7021 Website: www.DistinctiveDetailsInc.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	: Category 3
Acute toxicity (Inhalation)	: Category 4
Skin irritation	: Category 2
Eye irritation	: Category 2A
Specific target organ toxicity - single exposure	: Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure	: Category 2 (Liver, Kidney, Central nervous system)
Aspiration hazard	: Category 1
GHS label elements Hazard pictograms	
Signal word	: Danger
Hazard statements	 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.



	 H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs (Liver, Kidney, Central nervous system) through prolonged or repeated exposure.
Precautionary statements	 Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove victim to fresh ai and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with wate for several minutes. Remove contact lenses, if present and ext to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell. P331 Do NOT induce vomiting. P332 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or al hol-resistant foam for extinction. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. Disposal: P501 Dispose of contents/ container to an approved waste di posal plant.

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS



Version 1.1

Revision Date: 06/01/2025

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
64742-47-8	Distillates (petroleum), hydrotreated light	0 - 60
64742-88-7	Solvent naphtha (petroleum), medium aliph.	0 - 60
1330-20-7	Mixed xylenes	30 - 50
100-41-4	**Ethylbenzene	10 - 20

Any Concentration shown as a range is due to batch variation.

Special Notes: : Functionally equivalent petroleum streams may be found in this preparation at varying concentrations.

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	 If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing	: High volume water jet



Version 1.1	Revision Date: 06/01/2025
media	
Specific hazards during fire- fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	: No hazardous combustion products are known
Specific extinguishing meth- ods	: Use a water spray to cool fully closed containers.
Further information	 Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if nec- essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition.
Advice on safe handling	 Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8.



_

Safety Data Sheet 2518 Solv-All

Version 1.1	Revision Date: 06/01/2025
Conditions for safe storage	 Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
64742-47-8	Distillatos (potroloum) by	TWA		OSHA Z-1
04/42-4/-0	Distillates (petroleum), hy- drotreated light	IVVA	500 ppm 2,000 mg/m3	USHA Z-1
		TWA	200 mg/m3	ACGIH
		IVVA	(total hydrocarbon	ACGIN
			vapor)	
		TWA	400 ppm	OSHA P0
			1,600 mg/m3	
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
64742-88-7	Solvent naphtha (petroleum),	TWA	500 ppm	OSHA Z-1
	medium aliph.		2,000 mg/m3	
		TWA	200 mg/m3	ACGIH
			(total hydrocarbon	
			vapor)	
		TWA	400 ppm	OSHA P0
			1,600 mg/m3	
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	100 ppm	OSHA Z-1
			435 mg/m3	
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm	NIOSH REL
			435 mg/m3	
		ST	125 ppm	NIOSH REL
			545 mg/m3	



/ersion 1.1				Revision Da	te: 06/01/2025
			TWA	100 ppm 435 mg/m3	OSHA Z-1
			TWA	100 ppm 435 mg/m3	OSHA P0
			STEL	125 ppm 545 mg/m3	OSHA P0
ersonal protective equipment					
Respiratory protection	:	quired.		tective equipment norn ation use a respirator wi	
and protection					
Remarks	:	The suitability for with the produce		workplace should be d otective gloves.	iscussed
Eye protection	:	Eye wash bottle Tightly fitting sa Wear face-shiel problems.	fety goggles		processing
Skin and body protection	:		otection ac	cording to the amount a bstance at the work pla	
Hygiene measures	:	When using do When using do Wash hands be	not smoke.	rink. and at the end of work	day.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: No data available
Odour	: No data available
Odour Threshold	: No data available
рН	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash point	: 27 °C (81 °F) Method: Tag closed cup
Evaporation rate Flammability (solid, gas)	1Ethyl EtherNo data available



Version 1.1

Revision Date: 06/01/2025

Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: > 1(Air = 1.0)
Relative density	: 0.811 @ 25 °C (77 °F)
Density	: 0.811 g/cm3 @ 25 °C (77 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	: No hazards to be specially mentioned.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Alkalis Reducing agents Strong acids Strong oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity

: Acute toxicity estimate: > 5,000 mg/kg



/ersion 1.1	Revision Date: 06/01/2025
Acute inhalation toxicity	: Acute toxicity estimate: 15637 ppm Exposure time: 4 h Test atmosphere: gas
Acute dermal toxicity	: Acute toxicity estimate: 2,567 mg/kg
<u>Components:</u> 64742-47-8: Acute inhalation toxicity	: Assessment: The component/mixture is moderately toxic after short term inhalation.
1330-20-7: Acute inhalation toxicity	 LC50 (Rat, male): 6700 ppm Exposure time: 4 h Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	 LD50 (Rabbit): 1,700 mg/kg Assessment: The component/mixture is moderately toxic after single contact with skin.
Skin corrosion/irritation	

Product:

Remarks: Irritating to skin.

Components:

64742-47-8: Result: Irritating to skin.

64742-88-7:

Species: Rabbit Result: Irritating to skin.

1330-20-7:

Species: Rabbit Exposure time: 24 h Result: Irritating to skin.

Serious eye damage/eye irritation

Product: Remarks: Irritating to eyes.

<u>Components:</u> 64742-47-8: Result: Irritation to eyes, reversing within 7 days

1330-20-7: Species: Rabbit Result: Irritating to eyes.



Version 1.1

Revision Date: 06/01/2025

Carcinogenicity		
Product: Carcinogenicity - Assess- ment	: Not classifiable as a human carcinogen.	
IARC	Group 2B: Possibly carcinogenic to humans	
	100-41-4	**Ethylbenzene
OSHA	No component of this product present at levels equal to 0.1% is on OSHA's list of regulated car	•
NTP	No component of this product present at levels equal to 0.1% is identified as a known or anticip by NTP.	-
ACGIH	Confirmed animal carcinogen with unknown relements	evance to hu-
	100-41-4	**Ethylbenzene

STOT - single exposure

Components:

64742-47-8:

Target Organs: Nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

64742-88-7:

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

1330-20-7:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Components:

1330-20-7:

Target Organs: Central nervous system, Kidney, Liver Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Components:

64742-47-8: May be fatal if swallowed and enters airways.

64742-88-7:

May be fatal if swallowed and enters airways.



Version 1.1

Revision Date: 06/01/2025

1330-20-7:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity	
<u>Components:</u> 64742-47-8: M-Factor (Chronic aquatic toxicity)	: 1
Acute aquatic toxicity- As- sessment	: Toxic to aquatic life.
Chronic aquatic toxicity- As- sessment	: Toxic to aquatic life with long lasting effects.
64742-88-7: Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l Exposure time: 96 h Test Type: semi-static test
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 1.4 mg/l Exposure time: 48 h Test Type: static test
Toxicity to fish (Chronic tox- icity)	: NOEL (Oncorhynchus mykiss (rainbow trout)): 0.098 mg/l Exposure time: 28 d Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.
Toxicity to daphnia and other aquatic invertebrates (Chron-ic toxicity)	: NOEL (Daphnia magna (Water flea)): 0.48 mg/l Exposure time: 21 d
Acute aquatic toxicity- As- sessment	: Toxic to aquatic life.
Chronic aquatic toxicity- As- sessment	: Toxic to aquatic life with long lasting effects.



Version 1.1

Revision Date: 06/01/2025

Persistence and degradability No data available	
Bioaccumulative potential	
No data available	
Mobility in soil	
No data available	
Other adverse effects	
Product:	
Ozone-Depletion Potential	 Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological infor- mation	 An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Uni- var Solutions ChemCare: 1-800-909-4897
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

IATA (International Air Transport Association): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

IMDG (International Maritime Dangerous Goods):



Version 1.1

Revision Date: 06/01/2025

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, Flash Point:27 °C(81 °F)

SECTION 15. REGULATORY INFORMATION

WHMIS Classification	B2: Flammable liquid
	D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Mixed xylenes	1330-20-7	100	233

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard Acute Health Hazard

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

-	. ,	
100-41-4		**Ethylbenzene
108-88-3		**Toluene
71-43-2		**Benzene
91-20-3		Naphthalene

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	Mixed xylenes
100-41-4	**Ethylbenzene
108-88-3	**Toluene
71-43-2	**Benzene

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7 Mixed xylenes 100-41-4 **Ethylbenzene 108-88-3 **Toluene **Benzene 71-43-2 91-20-3 Naphthalene The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3: 1330-20-7 Mixed xylenes **Ethylbenzene 100-41-4 **Toluene 108-88-3 **Benzene 71-43-2 91-20-3 Naphthalene This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307 100-41-4 **Ethylbenzene

US State Regulations



Version 1.1

Revision Date: 06/01/2025


Massachusott	s Right To Knov		
Massachusett	1330-20-7	, Mixed xylenes	30 - 50 %
	100-41-4	**Ethylbenzene	10 - 20 %
	71-43-2	**Benzene	0 - 0.1 %
Pennsylvania	Right To Know		
	64742-47-8	Distillates (petroleum), hydrotreated light	0 - 60 %
	64742-88-7	Solvent naphtha (petroleum), medium aliph.	0 - 60 %
	1330-20-7	Mixed xylenes	30 - 50 %
	100-41-4	**Ethylbenzene	10 - 20 %
	108-88-3	**Toluene	0.1 - 1 %
New Jersey R	ight To Know		
	64742-47-8	Distillates (petroleum), hydrotreated light	0 - 60 %
	64742-88-7	Solvent naphtha (petroleum), medium aliph.	0 - 60 %
	1330-20-7	Mixed xylenes	30 - 50 %
	100-41-4	**Ethylbenzene	10 - 20 %
	108-88-3	**Toluene	0.1 - 1 %
California Pro	p 65 100-41-4 71-43-2 91-20-3 108-88-3 71-43-2	WARNING! This product contains a chemical known to the State of California to cause cancer. **Ethylbenzene **Benzene Naphthalene WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. **Toluene **Benzene	
The compone	nts of this produ	ct are reported in the following inventories:	
TSCA		: On TSCA Inventory	
DSL		All components of this product are on the Can	adian DSL
AICS		: On the inventory, or in compliance with the inv	entory
ENCS		Not in compliance with the inventory	
ISHL		Not in compliance with the inventory	
KECI		: On the inventory, or in compliance with the inv	entory
PICCS	: On the inventory, or in compliance with the inventory		
IECSC	: On the inventory, or in compliance with the inventory		
CH INV		: The formulation contains substances listed on ventory	the Swiss In-



Version 1.1

Revision Date: 06/01/2025

SECTION16. OTHER INFORMATION



The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Univar Solutions Product Compliance Department (1-855-429-2661) SDSNA@univarsolutions.com.

Revision Date	: 06/01/2025
Legacy SDS:	: R0357388

Material number: 681160, 543051, 102755

Key or legend to abbreviations and acronyms used in the safety data sheet					
ACGIH	American Conference of Govern- ment Industrial Hygienists	LD50	Lethal Dose 50%		
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level		
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency		
NDSL	Canada, Non-Domestic Substanc- es List	NIOSH	National Institute for Occupational Safety & Health		
CNS	Central Nervous System	NTP	National Toxicology Program		
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemi- cals		
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level		
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration		
EGEST	EOSCA Generic Exposure Scenar- io Tool	OSHA	Occupational Safety & Health Administration		



Version 1.1

Revision Date: 06/01/2025

EOSCA	European Oilfield Specialty Chem- icals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commer- cial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composi- tion, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		