#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name : Tree Sap Remover

Chemical name : 2-Propanol

Identified uses

Solvent; Additive

De-icing and anti-icing applications; Antifreeze/coolant.;

Cosmetics, personal care products

Prohibited uses

: Pharmaceutical excipient; Active pharmaceutical ingredient (API); Tobacco; Electronic cigarettes (E-cigarettes); Cannabis

Direct Food additives

#### 1.2. Details of the supplier of the safety data sheet

#### Supplier

Distinctive Details Inc. 1253 Lower Elkton Rd. Columbiana, OH 44408

www.DistinctiveDetailsInc.com Phone: 1-800-711-7021

#### 1.3. Emergency telephone number

Emergency number : 1-800-424-9300 (Chemtrec 24 Hr. Emergency Line)

## 2. HAZARDS IDENTIFICATION

### **GHS Classification**

Flammable liquids

Eye irritation

Category 2

Category 2

Specific target organ toxicity - single exposure

Category 3

# Label elements

Hazard symbols





Signal word : Danger

Hazard Statements : H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements

## : Prevention

P210 Keep away from open flames/ hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

## Response

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

## Storage

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

# Disposal

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

Hazards Not Otherwise Classified (HNOC)

Repeated contact with neat product may dry the skin causing cracking and/or fissuring.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

# Substances

### Components

Chemical name	CAS-No. EC-No.	Weight %	Component Type
2-Propanol	67-63-0	>= 99.8 %	А
Ethyl alcohol	64-17-5	<=0.15 %	С

Key:

(A) Substance

(C) Impurity

#### 4. FIRST AID MEASURES

General advice : Consult a physician/doctor if necessary.

Take proper precautions to ensure your own health and safety

before attempting rescue and providing first aid. Show this material safety data sheet to the doctor in

attendance.

Do not leave the victim unattended.

If inhaled : If overcome by exposure, remove victim to fresh air

immediately.

Give oxygen or artificial respiration as needed. Seek medical attention if discomfort persists.

In case of skin contact : Take off contaminated clothing and wash before reuse.

Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes.

If sticky, use waterless cleaner first.

Seek medical attention if ill effect or irritation develops.

In case of eye contact : Immediately flush the eyes with large amounts of clean low-

pressure water for at least 15 minutes, occasionally lifting the upper and lower lids. If pain or irritation persists, promptly

obtain medical attention.

If swallowed : If product is ingested, do not induce vomiting and contact a

physician or Poison Control Center.

Notes to physician

Symptoms : Inhalation of very high concentrations may cause asphyxia,

anesthesia, CNS depression (primarily fatigue, dizziness and loss of concentration, with collapse, coma and death in cases of severe overexposure), and possible cardiac sensitization.

Hazards : May be harmful if swallowed.

May be harmful if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Treatment : Treat symptomatically.

Treatment of overexposure should be directed at the control of

symptoms and the clinical condition of the patient.

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : SMALL FIRE: Use dry chemicals, CO2, water spray or alcohol-

resistant foam. LARGE FIRE: Use water spray, water fog or

alcohol-resistant foam.

Unsuitable extinguishing

media

: WARNING - Water may be ineffective unless used under

favorable conditions by experienced fire fighters trained in fighting all types of flammable liquid fires. Water can be used

to cool and protect exposed material.

Specific hazards during fire

fighting

: Releases flammable vapors below normal ambient

temperatures.

Fine sprays/mists may be combustible at temperatures below

normal flash point.

Vapors may be heavier than air.

May travel long distances along the ground before igniting and

flashing back to vapor source.

When mixed with air and exposed to ignition source, vapors

can burn in open or explode if confined.

Diluting with water may not suffice to raise flash point above

ambient temperatures.

Water may be ineffective in firefighting due to low flash point.

Although water soluble, may not be practical to extinguish fire

by water dilution.

Move containers from fire area if it can be done without risk.

Fight fire from maximum distance or use unmanned hose

holders or monitor nozzles.

Cool containers with flooding quantities of water until well after

fire is out.

Withdraw immediately in case of rising sound from venting

safety devices or discoloration of tank.

Always stay away from tanks engulfed in fire.

For massive fire, use unmanned hose holders or monitor

nozzles; if this is impossible, withdraw from area and let fire

burn.

Special protective equipment

for fire-fighters

: Wear positive pressure self-contained breathing apparatus

(SCBA).

Structural firefighter's protective clothing will only provide

limited protection.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Avoid direct contact with released material. Stay upwind.

Eliminate all sources of ignition. Evacuate personnel to safe areas.

Prevent further leakage or spillage if safe to do so.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Do not flush into surface water or sanitary sewer system.

Methods for containment /

Methods for cleaning up

: Extremely flammable liquid.

Release causes immediate fire/explosion hazard.

Liquids/vapors may ignite. Extinguish all ignition sources.

All equipment used when handling this product must be

grounded.

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Prevent entry into waterways, sewers, basements or confined

areas.

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible

material and transfer to containers.

Use clean non-sparking tools to collect absorbed material. Dike large spills and place materials in salvage containers. Water spray may reduce vapor; but may not prevent ignition in

closed spaces.

## 7. Handling and storage

### Precautions for safe handling

Advice on safe handling : For industrial use only.

Keep container tightly closed when not in use.

Check atmosphere for explosiveness and oxygen deficiencies.

Extinguish all ignition sources.

Containers must be properly grounded before beginning

. . .

Use only non-sparking tools.

Carefully vent any internal pressure before removing closure.

Wear recommended personal protective equipment.
All equipment must conform to applicable electrical code.
Isolate, vent, drain, wash and purge systems or equipment

before maintenance or repair.

Handle empty containers with care; vapor residue may be

flammable/explosive.

Fire-fighting class : OSHA/NFPA Class IB Flammable Liquid.

# Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Steel drums are recomended for packaging.

Store only in tightly closed, properly vented containers away from heat, sparks, open flame and strong oxidizing agents.

Store closed drums with bung in up position.

Do not store this material in aluminum containers.

Material may attack some forms of plastic, aluminum, rubber

and coatings.

Specific end use(s)

: See Section 1.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Control parameters**

### Ingredients with workplace control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Type	Limit Value	Basis	Additional
				Revision Date	Information
Isopropyl Alcohol	67-63-0	STEL	400 ppm	US (ACGIH) 2012	
Isopropyl Alcohol	67-63-0	TWA	200 ppm	US (ACGIH) 2012	
Isopropyl Alcohol	67-63-0	IDLH	2,000 ppm	NIOSH September 2007	
	Remarks: 10 <sup>o</sup>	% LEL	1		

Isopropyl Alcohol	67-63-0	TWA	400 ppm 980 mg/m3	US (OSHA) June 23, 2006	
Ethyl alcohol	64-17-5	STEL	1,000 ppm	US (ACGIH) 2012	
Ethyl alcohol	64-17-5	IDLH	3,300 ppm	NIOSH September 2007	
	Remarks: 109	% LEL			
Ethyl alcohol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	US (OSHA) June 23, 2006	

Consult local authorities for acceptable exposure limits.

# **Biological Exposure Indices**

Components	CAS-No.	Control	Biological	Sampling	Concentration	Basis
		parameters	specimen	time		
Isopropyl Alcohol	67-63-0	Acetone	urine	end of shift at end of workweek	40 mg/l	ACGIH_BEI S
		Remarks: background, nonspecific.				

### **Exposure controls**

# **Engineering measures**

No special ventilation is recommended under anticipated conditions of normal use beyond that needed for normal comfort control.

#### Personal protective equipment

Respiratory protection : When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Hand protection : Wear chemical resistant gloves such as:

Butyl rubber. Nitrile.

or

Viton(TM).

Eye and face protection : Eye protection such as chemical splash goggles and/or face

shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or

vapor.

Skin and body protection : Not normally considered a skin hazard.

Where use can result in skin contact, practice good personal

hygiene.

The equipment must be cleaned thoroughly after each use.

Hygiene measures : Selection of appropriate personal protective equipment should

be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered

during use.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Use good personal hygiene practices.

Wash hands before eating, drinking, smoking, or using toilet

facilities.

Take off contaminated clothing and wash before reuse.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : Clear, colorless.

Odor : Medicinal odor analogous to rubbing alcohol.

Odor Threshold : ~ 200 ppm

Flash point : 12 °C

Method: (TCC)

Ignition temperature : 399 °C

Lower explosion limit : 2 vol%

Upper explosion limit : 12 vol%

Flammability (solid, gas) : Not applicable

Oxidizing properties : Not considered an oxidizing agent.

Autoignition temperature : ~ 399 °C

Molecular weight : 60.09 g/mol

Decomposition temperature : not determined

Melting point/freezing point : -88 °C

Boiling point/boiling range : 82 °C

at 1,013 hPa

Vapor pressure : 44 hPa

at 20 °C

Density : 0.79 g/cm3

at 20 °C

(Water = 1.0 at  $4^{\circ}$ C ( $39.2^{\circ}$ F))

Water solubility : Miscible

Partition coefficient: n- : log Pow: 0.05

octanol/water

at 25 °C

Viscosity, dynamic : 2.4 mPa.s

at 20 °C

Viscosity, kinematic : 2.6 mm2/s

at 25 °C

Relative vapor density : 2.07

at 15 - 20 °C (Air = 1.0)

Explosive properties : Not explosive

Other Information : No additional information available.

#### 10. STABILITY AND REACTIVITY

Reactivity : Will not occur.

Chemical stability : Stable under recommended storage conditions.

Hazardous reactions : Will not occur.

Conditions to avoid : Heat, sparks, open flame, other ignition sources, and oxidizing

conditions.

Materials to avoid : Strong oxidizing agents.

Acetaldehyde. Chlorine.

Ethylene Oxide.

Acids

Isocyanates.

Hazardous decomposition

Thermal decomposition

products

: Not expected to decompose under normal conditions.

: Incomplete combustion will form carbon monoxide and other

toxic vapors.

#### 11. TOXICOLOGICAL INFORMATION

Product Summary : The below given information is based on the assessment of

the product including impurities.

**Acute toxicity** 

Acute oral toxicity : Based on acute toxicity values, not classified.

: LD50: 4,396 mg/kg

Species: Rat

: Ingestion may cause gastrointestinal effects (pain, nausea, vomiting, hemorrhage), hypothermia, cardiac effects (low blood pressure, shock and cardiac arrest), liver changes, kidney damage, and CNS effects (headache, dizziness,

sleepiness, coma and death).

Acute inhalation toxicity : Based on acute toxicity values, not classified.

: LC50: 46.6 mg/l

Exposure time: 8 HOURS

Species: Rat

: High vapor concentrations may cause irritation of the eyes, nose, and/or throat, changes to the liver, lung, spleen, and brain, and central nervous system depression (ataxia, dizziness, narcosis, and muscle relaxation, with respiratory arrest and death in cases of severe over exposure).

Acute dermal toxicity : Based on acute toxicity values, not classified.

: LD50: 12,870 mg/kg

Species: Rabbit.

: High exposures may cause systemic toxicity (CNS depression

and death).

**Skin corrosion/irritation**: Based on skin irritation values, not classified.

Liquid may cause slight skin irritation.

Exposure of liquid to the underdeveloped skin of premature

infants may cause severe irritation.

Serious eye damage/eye

irritation

: Classified

Causes serious eye irritation.

Respiratory or skin : Respiratory sensitization

sensitization Not classified

No study available.

: Skin sensitization Not classified

No adverse effect observed.

Chronic toxicity

Carcinogenicity : Not classified

Ethanol possesses properties that indicate a carcinogenicity hazard for human health but these are manifest only at doses

associated with consumption of alcoholic beverages.

In the context of an industrial chemical, these hazards do not warrant concern as these are not likely to result from the manufacture and use of ethanol and ethanol containing

products.

Germ cell mutagenicity : Not classified

No adverse effect observed.

Reproductive toxicity

Effects on fertility /
Effects on or via lactation

: Not classified

Ethanol possesses properties that indicate a lactation hazard for human health but these are manifest only at doses associated with consumption of alcoholic beverages. In the context of an industrial chemical, these hazards do not warrant concern as these are not likely to result from the manufacture and use of ethanol and ethanol containing

products.

Effects on Development : Not classified

Ethanol possesses properties that indicate a developmental hazard for human health but these are manifest only at doses

associated with consumption of alcoholic beverages.

In the context of an industrial chemical, these hazards do not warrant concern as these are not likely to result from the manufacture and use of ethanol and ethanol containing

products.

Target Organ Systemic Toxicant - Single exposure

: Classified, May cause drowsiness or dizziness.

: Exposure routes: Inhalation, Oral, Dermal Target Organs: Central nervous system

Target Organ Systemic Toxicant - Repeated

: Based on repeated exposure toxicity values, not classified.

exposure

Aspiration hazard : Not classified

May be harmful if swallowed and enters airways.

12. Ecological information

**Ecotoxicology Assessment** 

Short-term (acute) aquatic

hazard

Long-term (chronic)

aquatic hazard

: Based on acute aquatic toxicity values, not classified.

: Not classified, based on readily biodegradability and low acute toxicity.

**Toxicity to fish** : Low acute toxicity to fish

Toxicity to daphnia and other aquatic invertebrates

: Low acute toxicity to aquatic invertebrates.

**Toxicity to algae** : Low toxicity to algae.

**Toxicity to bacteria** : Low toxicity to sewage microbes.

Toxicity to fish (Chronic

toxicity)

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity)

: Chronic toxicity to fish is expected to be low.

: Chronic toxicity expected to be low.

Persistence and degradability

**Biodegradability** : Biodegradation: 86 - 94 %

Exposure time: 14 d Rapidly degradable.

(After two weeks in a ready biodegradability test)

Stability in soil

ethyl alcohol : Low potential for soil adsorption expected

Bioaccumulative potential

**Bioaccumulation** : Bioconcentration factor (BCF): 3.16

This material is not expected to bioaccumulate.

Mobility in soil

Distribution among environmental compartments

: Type: Stability in water

Initially partitioning mainly to water and air.

: Type: Stability in soil

Volatilization from water or soil surfaces is expected to be

limited.

Other adverse effects

pathways

**Environmental fate and** : No additional information available.

Other information

Additional ecological

information

: No additional information available.

## 13. Disposal considerations

#### Waste treatment methods

Product : Contaminated product/soil/water may be U.S. Resource

> Conservation and Recovery Act (RCRA)/U.S. Occupational Safety and Health Administration (OSHA) hazardous waste

due to potentially low flash point.

(See 40 U.S. Code of Federal Regulations (CFR) 261 and 29

CFR 1910).

Comply with federal, state, or local regulations for disposal.

### 14. TRANSPORT INFORMATION

CFR\_ROAD

UN number : 1219

Description of the goods : ISOPROPANOL

: (ISOPROPYL ALCOHOL)

Class : 3 Packing group : 11 Labels 3

Marine pollutant : no

**CFR RAIL** 

UN number : 1219

Description of the goods : ISOPROPANOL

(ISOPROPYL ALCOHOL)

13 / 17

Class : 3 Packing group : 11 Labels : 3

Marine pollutant : no

**IMDG** 

UN number : 1219

Description of the goods : ISOPROPANOL

Class : 3

Packing group : II Labels : 3 EmS Number 1 : F-E EmS Number 2 : S-D

: no Marine pollutant

BLG (MARPOL Annex II)

Description of the goods
Pollution category
Ship type
: ISOPROPYL ALCOHOL
Z
NONE

Description of the goods : ISOPROPANOL Class : 3
Packing group : 11 Packing group Labels : 3

### 15. REGULATORY INFORMATION

#### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

# Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

## SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

#### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Hazard not otherwise classified (health hazards)

#### **SARA 313**

This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313 and 40 CFR 372:

Component	CASRN	Reporting Threshold
Isopropyl Alcohol	67-63-0	1.0%

#### **State Reporting**

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

67-63-0 Isopropyl Alcohol 64-17-5 Ethyl alcohol

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

67-63-0 Isopropyl Alcohol

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

67-63-0 Isopropyl Alcohol

# Other international regulations

### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement



Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that the chemical substance in this product has been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

#### 16. OTHER INFORMATION

# Material safety datasheet sections which have been updated:


Revised Section(s): 1

HMIS Classification : Health Hazard: 2

Flammability: 3 Physical hazards: 0

NFPA Classification : Health Hazard: 1

Fire Hazard: 3 Instability: 0



# **Further information**

HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

## Disclaimer

#### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/
The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

## Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

**End of Material Safety Data Sheet**