DISTINCTIVE DETAILS

2852 Black Streak/Stain Remover

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 8/31/2022 Revision date: 8/31/2022

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : 2852 Black Streak/Stain Remover

Product code : 2852

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Hard surface cleaner/degreaser

1.3. Supplier

Supplier

Distinctive Details Inc. 1253 Lower Elkton Rd. Columbiana, OH 44408 T 1 800-711-7021

www.DistinctiveDetailsInc.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (Chemtrec 24 Hr. Emergency Line) International: +1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Met. Corr. 1 Skin Corr. 1B Eye Dam. 1 Skin Sens. 1 STOT RE 1 HHNOC 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS)







Signal word (GHS) : Danger

Hazard statements (GHS) : May be corrosive to metals.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure.

Causes severe damage to the respiratory track

Precautionary statements (GHS) : Keep only in original container.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash hands, forearms and face thoroughly after handling.

Do not eat, drink or smoke when using this product

EN (English)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

Get medical advice/attention if you feel unwell.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
2-butoxyethanol	2-butoxyethanol 2-Butoxy-1-ethanol / Butoxyethanol / Ethanol, 2-butoxy- / Ethylene glycol monobutyl ether / Ethylene glycol n-butyl ether / Hydroxyethyl butyl ether / Ethylene glycol butyl ether / 2-Butoxyethan-1-ol / Ethylene glycol mono-n-butyl ether / 2-n-Butoxyethanol / Butyl glycol / BUTOXYETHANOL / EGBE / EGMBE / Butoxyethanol, 2- / Butyl Cellosolve / Monobutyl ether of ethyleneglycol	CAS-No.: 111-76-2	3 - 7
Sodium metasilicate pentahydrate	Sodium metasilicate pentahydrate Sodium silicate pentahydrate / Disodium silicate, pentahydrate / Silicic acid (H2SiO3), disodium salt, pentahydrate / Silicic acid, disodium salt, pentahydrate / Sodium metasilicate, pentahydrate	CAS-No.: 10213-79-3	3 - 7

11/21/2023 EN (English) 2/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched	Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched 4-Nonylphenol, branched, ethoxylated / Polyethylene glycol, mono(p-nonylphenyl) ether, branched / .alpha(4-Nonylphenyl)omegahydroxy poly(oxy-1,2-ethanediyl), branched / .alpha(p-Nonylphenyl)omegahydroxypoly(oxyethylene) branched / 4-Nonylphenol, branched and linear, ethoxylated / .alpha(4-Nonylphenyl)omegahydroxypoly(oxy-1,2-ethanediyl) branched / Ethoxylated branched and linear 4-nonylphenol / Poly (oxy-1,2-ethanediyl), alpha-(4-nonylphenyl)-omega-hydroxy-, branched / 4-Nonylphenol, branched, ethoxylated, 1 - 2.5 moles ethoxylated	CAS-No.: 127087-87-0	1 - 5
Sodium xylenesulfonate	Sodium xylenesulfonate Sodium xylene sulfonate / Benzenesulfonic acid, dimethyl-, sodium salt / Sodium dimethylbenzenesulfonate / Sodium xylenesulphonate / Xylenesulfonate, sodium / Xylenesulfonic acid, sodium salt / Benzenesulphonic acid, dimethyl-, sodium salt / Benzenesulfonic acid, dimethyl-, sodium salt (1:1) / SODIUM XYLENESULFONATE / Dimethylbenzenesulfonic acid, sodium salt	CAS-No.: 1300-72-7	1 - 5
D-Limonene	D-Limonene Cyclohexene, 1-methyl-4-(1-methylethenyl)-, (4R)-/ Cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)-/ (R)-p-Mentha-1,8-diene / p-Mentha-1,8-diene, (R)- (+)- / Limonene, D- / Menthadiene, 1,8(9)-p- / d- Limonene / Limonene, d- / (4R)-1-Methyl-4-(1- methylethenyl)cyclohexene / (4R)-p-Mentha-1,8- diene / 1-Methyl-4-prop-1-en-2-yl-cyclohexene / (R)-1-Methyl-4-(1-methylethenyl)cyclohexene / d- LIMONENE / (R)-1-Methyl-4-(1- methylethenyl)cyclohex-1-ene / (R)-4-Isopropenyl- 1-methylcyclohex-1-ene / Limonene / LIMONENE / limonene, (+)-	CAS-No.: 5989-27-5	0.5 - 1.5
Sodium hydroxide	Caustic soda / Sodium hydroxide (Na(OH)) / SODIUM HYDROXIDE / LYE	CAS-No.: 1310-73-2	0.5 - 1.5

11/21/2023 EN (English) 3/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivatives, hydroxides, inner salts	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivatives, hydroxides, inner salts N-Cocamidopropyl-N,N-dimethylglycine, hydroxide, inner salt / N-(Coco alkyl) amido propyl dimethyl betaine / N-(3-Cocoamidopropyl)-N,N-dimethyl-N-carboxymethylammonium hydroxide, inner salt / Coconut amidobetaine / 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivatives, inner salts / Cocoamido betaine / COCAMIDOPROPYL BETAINE / Cocamidopropyl betaine / 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-cocoacyl derivatives, hydroxides, inner salts / 3-Amino-N-(carboxymethyl)-N,N-dimethyl-N-cocoacyl(derivatives)-1-propanaminium-hydroxide inner salt / cocamidopropyl betaine	CAS-No.: 61789-40-0	0.1 - 1

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

The state of the s	
First-aid measures after inhalation	: If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	 : IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects (acute and delayed)

4.2. Most important symptoms and effects (acute and delayed)		
Symptoms/effects after inhalation	: Causes severe damage to the respiratory tract.	
Symptoms/effects after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters. May cause an allergic skin reaction.	
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.	
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.	

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

11/21/2023 EN (English) 4/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combus

 Products of combustion may include, and are not limited to: oxides of carbon. Toxic and corrosive vapours may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

Emergency procedures

: Do not touch or walk on the spilled product.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up

: Sweep or shovel spills into appropriate container for disposal. Provide ventilation. Absorb spillage to prevent material damage.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: May be corrosive to metals.

Precautions for safe handling

: Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures

: Wash contaminated clothing before reuse. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed. Keep only in original container. Store locked up. Store in corrosive resistant container with a resistant inner liner.

11/21/2023 EN (English) 5/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available Sodium hydroxide (1310-73-2) Sodium hydroxide (1310	o. 1. Control parameters			
Sodium hydroxide (1310-73-2) USA - ACGIH - Occupational Exposure Limits ACGIH OEL C 2 mg/m³ USA - OSHA - OCCUpational Exposure Limits USA - IDLH - Occupational Exposure Limits IDLH 10 mg/m³ USA - IDLH - Occupational Exposure Limits IDLH 10 mg/m³ USA - NIOSH - Occupational Exposure Limits INIOSH REL C 2 mg/m³ USA - NIOSH - Occupational Exposure Limits INIOSH REL C 2 mg/m³ USA - ACGIH - Occupational Exposure Limits IDLH 0 mg/m³ 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 pm Remark (ACGIH) TLVB Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans), BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 pm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annolated Table Z-1 USA - NIOSH - Occupational Exposure Limits IUSA - NIOSH PEL TWA [1] 50 ppm	2852 Black Streak/Stain Remover	2852 Black Streak/Stain Remover		
USA - ACGIH - Occupational Exposure Limits ACGIH OEL C 2 mg/m² USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 2 mg/m² USA - IDLH - Occupational Exposure Limits IDLH 10 mg/m² USA - NIOSH - Occupational Exposure Limits INOSH REL C 2 mg/m² USA-NIOSH chemical category SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans). BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Limits Local name 2-Butoxyethanol USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm Limit value category (CISHA) prevent or reduce skin absorption Regulatory reference (USA-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits INOSH REL TWA [19] 700 ppm USA - NIOSH - Occupational Exposure Limits INOSH REL TWA [19] 700 ppm	No additional information available			
ACGIH OEL C 2 mg/m² USA - OSHA - Occupational Exposure Limits USA- IDLH - Occupational Exposure Limits IDLH 10 mg/m³ USA- NIOSH - Occupational Exposure Limits IUSH REL C 2 mg/m² US-NIOSH chemical category SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA- ACGIH - Occupational Exposure Limits ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) 20 ppm Remark (ACGIH) 20 ppm Remark (ACGIH) 20 ppm Remark (ACGIH - Biological Exposure Indices USA- ACGIH - Scupational Exposure Limits Local name 20 mg/gr creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA- ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol USA- ACGIH - Biological Exposure Indices USA- ACGIH - Biological Exposure Indices USA- OCCUPATIONAL Exposure Indices USA- OCCUPATIONAL Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA- IDLH - Occupational Exposure Limits IUSA - IDLH - Occupational Exposure Limits IUSA - IDLH - Occupational Exposure Limits IUSH - Occupational Exposure Limits IUSH - IDLH - Occupational Exposure Limits	Sodium hydroxide (1310-73-2)			
USA - OSHA - Occupational Exposure Limits USA - IDLH - Occupational Exposure Limits IDLH 10 mg/m² USA - NIOSH - Occupational Exposure Limits IDLH 20 a mg/m² USA - NIOSH - Occupational Exposure Limits NIOSH REL C 2 mg/m² US-NIOSH chemical category SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans): BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - Oscupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) Prevent or reduce skin absorption SSA - NIOSH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [2] 54 mg/m² NIOSH REL TWA [2] 55 ppm	USA - ACGIH - Occupational Exposure Limits			
OSHA PEL TWA [1] 2 mg/m² USA - IDLH - Occupational Exposure Limits 10 mg/m² USA - NIOSH - Occupational Exposure Limits 10 mg/m² USA - NIOSH - Occupational Exposure Limits 2 mg/m² US-NIOSH obenical category SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans (ERPOSUM) Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits USA - Oscupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - NIOSH - Occupational Exposure Limits TO0 ppm USA - NIOSH - Occupational Exposure Limits	ACGIH OEL C	2 mg/m³		
USA - IDLH - Occupational Exposure Limits IDLH 10 mg/m² USA - NIOSH - Occupational Exposure Limits NIOSH REL C 2 mg/m² US-NIOSH chemical category SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans): BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm USA - IDLH - Occupational Exposure Limits USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [10] 5 ppm	USA - OSHA - Occupational Exposure Limits			
IDLH 10 mg/m² USA - NIOSH - Occupational Exposure Limits NIOSH REL C 2 mg/m² US-NIOSH chemical category SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OLL TWA [ppm] 20 ppm Remark (ACGIH) 11-V6-19 11-V8 Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); EEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA NIOSH REL TWA NIOSH REL TWA NIOSH REL TWA [2pm] 5 ppm	OSHA PEL TWA [1]	2 mg/m³		
USA - NIOSH - Occupational Exposure Limits NIOSH REL C 2 mg/m² SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - ACGIH - Biological Exposure Limits USA - OSHA - Occupational Exposure Limits USA - DSHA - UX [1] 240 mg/m² OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH (ppm) 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [24 mg/m² 5 ppm	USA - IDLH - Occupational Exposure Limits			
NIOSH REL C US-NIOSH chemical category SK: DIR(COR) Apr 2011 2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m² OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA - Occupational Exposure Limits USA - IDLH - Occupational Exposure Limits USA - IDLH - Occupational Exposure Limits USA - NIOSH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m² NIOSH REL TWA 5 ppm 5 ppm	IDLH	10 mg/m³		
USA - ACGIH - Biological Exposure Limits Local name 2-Butoxyethanol (1998) Regulatory reference 2-Butoxyethanol 2-Butoxyethan	USA - NIOSH - Occupational Exposure Limits			
2-butoxyethanol (111-76-2) USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) 1LV Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [24 mg/m³ NIOSH REL TWA [25 ppm] 5 ppm	NIOSH REL C	2 mg/m³		
USA - ACGIH - Occupational Exposure Limits Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [ppm] 5 ppm	US-NIOSH chemical category	SK: DIR(COR) Apr 2011		
Local name 2-Butoxyethanol (EGBE) ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [21 24 mg/m² NIOSH REL TWA [22 55 ppm 5 ppm	2-butoxyethanol (111-76-2)			
ACGIH OEL TWA [ppm] 20 ppm Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [17] 24 mg/m³ NIOSH REL TWA [18] 5 ppm	USA - ACGIH - Occupational Exposure Limits			
Remark (ACGIH) TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	Local name	2-Butoxyethanol (EGBE)		
Relevance to Humans); BEI ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance to Humans Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [ppm] 5 ppm	ACGIH OEL TWA [ppm]	20 ppm		
Regulatory reference ACGIH 2020 USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [ppm] 5 ppm	Remark (ACGIH)			
USA - ACGIH - Biological Exposure Indices BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [ppm] 5 ppm	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans		
BEI 200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [ppm] 5 ppm	Regulatory reference	ACGIH 2020		
USA - OSHA - Occupational Exposure Limits Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	USA - ACGIH - Biological Exposure Indices			
Local name 2-Butoxyethanol OSHA PEL TWA [1] 240 mg/m³ OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	BEI			
OSHA PEL TWA [1] OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA NIOSH REL TWA [ppm] 5 ppm	USA - OSHA - Occupational Exposure Limits			
OSHA PEL TWA [2] 50 ppm Limit value category (OSHA) prevent or reduce skin absorption Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA [ppm] 5 ppm	Local name	2-Butoxyethanol		
Limit value category (OSHA) Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ 5 ppm	OSHA PEL TWA [1]	240 mg/m³		
Regulatory reference (US-OSHA) USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	OSHA PEL TWA [2]	50 ppm		
USA - IDLH - Occupational Exposure Limits IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	Limit value category (OSHA)	prevent or reduce skin absorption		
IDLH [ppm] 700 ppm USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	USA - IDLH - Occupational Exposure Limits			
NIOSH REL TWA 24 mg/m³ NIOSH REL TWA [ppm] 5 ppm	IDLH [ppm]	700 ppm		
NIOSH REL TWA [ppm] 5 ppm	USA - NIOSH - Occupational Exposure Limits			
	NIOSH REL TWA	24 mg/m³		
US-NIOSH chemical category SK: SYS-DIR(IRR) Apr 2011	NIOSH REL TWA [ppm]	5 ppm		
	US-NIOSH chemical category	SK: SYS-DIR(IRR) Apr 2011		

11/21/2023 EN (English) 6/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Sodium metasilicate pentahydrate (10213-79-3)

No additional information available

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivatives, hydroxides, inner salts (61789-40-0)

No additional information available

Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched (127087-87-0)

No additional information available

D-Limonene (5989-27-5)

USA - AIHA - Occupational Exposure Limits

WEEL TWA [ppm] 30 ppm

Sodium xylenesulfonate (1300-72-7)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and

safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour: No data availableOdour: No data availableOdour threshold: No data available

pH : 12.58

Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butylacetate=1) : No data available

11/21/2023 EN (English) 7/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

: Not flammable. Flammability Vapour pressure No data available Relative vapour density at 20 °C No data available Relative density No data available Solubility No data available Partition coefficient n-octanol/water No data available No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic Viscosity, dynamic : No data available **Explosive limits** : No data available Explosive properties : No data available Oxidising properties No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use. May be corrosive to metals.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents. Acids.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Toxic and corrosive vapours may be released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

Sodium hydroxide (1310-73-2)	
LD50 oral rat	325 mg/kg
LD50 dermal rabbit	1350 mg/kg
ATE CA (oral)	325 mg/kg bodyweight
ATE CA (Dermal)	1350 mg/kg bodyweight

11/21/2023 EN (English) 8/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2-butoxyethanol (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301
LD50 dermal rabbit	435 mg/kg
LC50 inhalation rat	2.35 mg/l
LC50 inhalation rat	486 ppm/4h
ATE CA (oral)	1414 mg/kg bodyweight
ATE CA (Dermal)	435 mg/kg bodyweight
ATE CA (Gases)	486 ppmv/4h
ATE CA (vapours)	2.35 mg/l/4h
ATE CA (dust,mist)	2.35 mg/l/4h
Sodium metasilicate pentahydrate (10213-79-	3)
LD50 oral rat	847 mg/kg
ATE CA (oral)	847 mg/kg bodyweight
1-Propanaminium, 3-amino-N-(carboxymethy	l)-N,N-dimethyl-, N-coco acyl derivatives, hydroxides, inner salts (61789-40-0)
LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
LD50 dermal rabbit	> 2000 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphe	nyl)omegahydroxy-, branched (127087-87-0)
LD50 oral rat	1310 mg/kg
ATE CA (oral)	657.2 mg/kg bodyweight
D-Limonene (5989-27-5)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	> 5 g/kg
Sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	≥ 3346 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), 95% CL: 3196 - 3503
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
Skin corrosion/irritation :	Causes severe skin burns.
Serious eye damage/irritation :	pH: 12.58 Causes serious eye damage. pH: 12.58
	May cause an allergic skin reaction.
S ,	Not classified.
Carcinogenicity : 2-butoxyethanol (111-76-2)	Not classified.
IARC group	3 - Not classifiable
into group	0 - NOT OLD SIMBLE

11/21/2023 EN (English) 9/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

D-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
Sodium xylenesulfonate (1300-72-7)	
NOAEL (chronic, oral, animal/female, 2 years)	≥ 60 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Remarks on results: other:
Reproductive toxicity :	Not classified.
1-Propanaminium, 3-amino-N-(carboxymethy	I)-N,N-dimethyl-, N-coco acyl derivatives, hydroxides, inner salts (61789-40-0)
NOAEL (animal/female, F1)	1000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:
STOT-single exposure :	Not classified.
Sodium hydroxide (1310-73-2)	
STOT-single exposure	May cause respiratory irritation.
2-butoxyethanol (111-76-2)	
STOT-single exposure	May cause respiratory irritation.
Sodium metasilicate pentahydrate (10213-79-	3)
STOT-single exposure	May cause respiratory irritation.
: STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
2-butoxyethanol (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Sodium xylenesulfonate (1300-72-7)	
NOAEL (oral, rat, 90 days)	763 – 3534 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard :	Not classified.
• •	Causes severe damage to the respiratory tract.
Symptoms/effects after skin contact :	Causes severe skin burns. Symptoms may include redness, pain, blisters. May cause an allergic skin reaction.
Symptoms/effects after eye contact :	Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion :	May be harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Other information :	Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general :	May cause long-term adverse effects in the aquatic environment.
Sodium hydroxide (1310-73-2)	
LC50 - Fish [1]	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [1]	40 mg/l

11/21/2023 EN (English) 10/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2-butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'
1-Propanaminium, 3-amino-N-(carboxymeth	yl)-N,N-dimethyl-, N-coco acyl derivatives, hydroxides, inner salts (61789-40-0)
LC50 - Fish [1]	1 – 10 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 - Crustacea [1]	6.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LOEC (chronic)	3.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.9 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched (127087-87-0)	
LC50 - Fish [1]	84.7 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	14 mg/l Test organisms (species): Daphnia magna
D-Limonene (5989-27-5)	
LC50 - Fish [1]	720 μg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.36 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	0.115 mg/l Test organisms (species): other:For freshwater invertebrates, species frequently include Daphnia magna or Daphnia pulex. Duration: '16 d'
Sodium xylenesulfonate (1300-72-7)	
LC50 - Fish [1]	≥ 1580 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1020 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

2852 Black Streak/Stain Remover	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

2852 Black Streak/Stain Remover	
Bioaccumulative potential	Not established.
2-butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water	0.81 (at 25 °C)

12.4. Mobility in soil

No additional information available

11/21/2023 EN (English) 11/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations

: Treatment, storage, transportation and disposal must be in accordance with Federal, State/Provincial and Local Regulations. Regulations may vary in different locations. Characterization and compliance with applicable laws are the responsibility solely of the generator. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

UN-No.(DOT/TDG) : UN1719

14.2. UN proper shipping name

Proper Shipping Name (DOT/TDG) : CAUSTIC ALKALI LIQUID, N.O.S. (Sodium Metasilicate, Sodium Hydroxide)

14.3. Transport hazard class(es)

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

Class (DOT/TDG) : 8 Hazard labels (DOT/TDG) : 8



14.4. Packing group

Packing group (DOT/TDG)

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

11/21/2023 EN (English) 12/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Sodium hydroxide (1310-73-2)	
CERCLA RQ	1000 lb

Poly(oxy-1,2-ethanediyl), .alphasulfoomegahydroxy-, C10-16-alkyl ethers, sodium salts (68585-34-2)	
3 , 3	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched (127087-87-0)	
Subject to reporting requirements of United States SARA Section 313	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Polyethylene glycol (25322-68-3)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Poly(oxy-1,2-ethanediyl), .alpha(dinonylphenyl)omegahydroxy- (9014-93-1)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Sodium hydroxide(1310-73-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
2-butoxyethanol(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List
Ethyl alcohol(64-17-5)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List

11/21/2023 EN (English) 13/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Component	State or local regulations
` '	U.S Pennsylvania - RTK (Right to Know) List; U.S Massachusetts - Right To Know List; U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date : 08/31/2022 Revision date : 08/31/2022 Other information : None.


Full text of H-statements	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
HHNOC 1	Health hazard not otherwise classified, category 1
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury. NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including

intrinsically noncombustible materials such as concrete, stone, and

NFPA reactivity : 3 - Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction but that require a strong initiating

source or must be heated under confinement before initiation.



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

EN (English) 14/14 11/21/2023



Danger

May be corrosive to metals. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure. Causes severe damage to the respiratory track.

Keep only in original container. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Distinctive Details Inc. 1253 Lower Elkton Rd.

Columbiana, OH 44408

1 800-711-7021

www.DistinctiveDetailsInc.com

