



Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 9/1/2020
Revision date: 8/26/2021
Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Super Ultimate
Product code : 5017

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Plastic, rubber, and vinyl coating.

1.3. Supplier

Manufacturer

Distinctive Details Inc.
1253 Lower Elkton Rd.
Columbiana, OH 44408
1.800.711.7021
1.800.711.7021
www.DistinctiveDetailsInc.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (Chemtrec 24 Hr. Emergency Line)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Liq. 2
Skin Irrit. 2
STOT SE 3
Asp. Tox. 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary statements (GHS) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical, lighting, ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Avoid breathing dust, fume, gas, mist, spray, vapours.
Wash hands, forearms and face thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear eye protection, face protection, protective clothing, protective gloves.
If swallowed: Immediately call a poison center or doctor.
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison center or doctor if you feel unwell.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Chemical name / Synonyms | Product identifier | % |
|-----------|---|--------------------|---------|
| n-Heptane | n-Heptane Heptane (n-) / Heptane / Normal heptane / Heptane, n- / HEPTANE | CAS-No.: 142-82-5 | 60 - 80 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

This product contains no phosphates

This product contains no NPEO (nonylphenol polyethoxylate)

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

First-aid measures after skin contact : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| | |
|------------------------------------|--|
| Symptoms/effects after eye contact | : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/effects after ingestion | : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause stomach distress, nausea or vomiting. |

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

| | |
|--------------------------------|---|
| Suitable extinguishing media | : Carbon dioxide (CO ₂), dry chemical powder, foam. |
| Unsuitable extinguishing media | : High volume water jet. |

5.2. Specific hazards arising from the chemical

| | |
|------------------|---|
| Fire hazard | : Highly flammable liquid and vapour. Products of combustion may include, and are not limited to: oxides of carbon. May release hazardous fumes. |
| Explosion hazard | : May form flammable/explosive vapour-air mixture. Vapours may travel long distances along ground before igniting/flashing back to vapour source. |

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|--|
| Protection during firefighting | : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). |
|--------------------------------|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|---|
| General measures | : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition. |
|------------------|---|

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|---|
| For containment | : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment. |
| Methods for cleaning up | : Sweep or shovel spills into appropriate container for disposal. Provide ventilation. |

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|---|
| Additional hazards when processed | : Handle empty containers with care because residual vapours are flammable. |
| Precautions for safe handling | : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. |
| Hygiene measures | : Take off immediately all contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--------------------|---|
| Technical measures | : Proper grounding procedures to avoid static electricity should be followed. |
| Storage conditions | : Keep out of the reach of children. Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Super Ultimate

No additional information available

n-Heptane (142-82-5)

USA - ACGIH - Occupational Exposure Limits

| | |
|----------------------|--------------------------------|
| ACGIH OEL TWA [ppm] | 400 ppm (Heptane, all isomers) |
| ACGIH OEL STEL [ppm] | 500 ppm (Heptane, all isomers) |

USA - OSHA - Occupational Exposure Limits

| | |
|------------------|------------------------|
| OSHA PEL TWA [1] | 2000 mg/m ³ |
| OSHA PEL TWA [2] | 500 ppm |

USA - IDLH - Occupational Exposure Limits

| | |
|------------|---------|
| IDLH [ppm] | 750 ppm |
|------------|---------|

USA - NIOSH - Occupational Exposure Limits

| | |
|---------------------|------------------------|
| NIOSH REL TWA | 350 mg/m ³ |
| NIOSH REL TWA [ppm] | 85 ppm |
| NIOSH REL C | 1800 mg/m ³ |
| NIOSH REL C [ppm] | 440 ppm |

8.2. Appropriate engineering controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Environmental exposure controls | : Avoid release to the environment. |

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration.

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---------------------------------------|---------------------------|
| Physical state | : Liquid |
| Appearance | : Clear blue liquid. |
| Colour | : Blue |
| Odour | : Bubble gum |
| Odour threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : 98 °C (208.4 °F) |
| Flash point | : -4 °C (24.8 °F) |
| Relative evaporation rate | : 3.46 |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : 1.6 PSI at 38°C (100°F) |
| Relative vapour density at 20 °C | : 0.69 16°C (61°F) |
| Relative density | : 0.782 |
| Solubility | : Not soluble. |
| Partition coefficient n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapour-air mixture.

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition. Direct sunlight.

10.5. Incompatible materials

Strong oxidizers. Chlorine bleach.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

n-Heptane (142-82-5)

| | |
|---------------------|---|
| LD50 oral rat | > 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity) |
| LD50 dermal rabbit | 3000 mg/kg |
| LC50 inhalation rat | 103 g/m ³ (Exposure time: 4 h) |
| ATE CA (Dermal) | 3000 mg/kg bodyweight |
| ATE CA (vapours) | 103 mg/l/4h |
| ATE CA (dust,mist) | 103 mg/l/4h |

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified.
Respiratory or skin sensitisation : Not classified.
Germ cell mutagenicity : Not classified.
Carcinogenicity : Not classified.
Reproductive toxicity : Not classified.
STOT-single exposure : May cause drowsiness or dizziness.

n-Heptane (142-82-5)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

: Not classified.

STOT-repeated exposure

n-Heptane (142-82-5)

| | |
|--|---|
| LOAEC (inhalation, rat, vapour, 90 days) | 16.6 mg/l air Animal: rat, Animal sex: male |
| NOAEC (inhalation, rat, vapour, 90 days) | 3.3 mg/l air Animal: rat, Animal sex: male |

Aspiration hazard : May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation : May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause stomach distress, nausea or vomiting.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

| n-Heptane (142-82-5) | |
|----------------------|--|
| LC50 - Fish [1] | 375 mg/l (Exposure time: 96 h - Species: Cichlid fish) |
| EC50 - Crustacea [1] | 1.5 mg/l Test organisms (species): Daphnia magna |
| LOEC (chronic) | 0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |

12.2. Persistence and degradability

| Super Ultimate | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| Super Ultimate | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

| n-Heptane (142-82-5) | |
|---------------------------------------|------|
| Partition coefficient n-octanol/water | 4.66 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapours are flammable.
The information in this SDS pertains only to the product as shipped.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT/TDG) : UN1993

14.2. UN proper shipping name

Proper Shipping Name (DOT/TDG) : Flammable liquids, n.o.s. (Contains: Heptanes)

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

14.3. Transport hazard class(es)

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

Class (DOT/TDG) : 3
Hazard labels (DOT/TDG) :



14.4. Packing group

Packing group (DOT/TDG) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

n-Heptane (142-82-5)

| | |
|--------------------------|--|
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a final TSCA section 4 test rule. |
|--------------------------|--|

Poly(dimethylsiloxane) (63148-62-9)

| | |
|--------------------------|---|
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). |
|--------------------------|---|

Ethyl acetate (141-78-6)

| | |
|-----------|---------|
| CERCLA RQ | 5000 lb |
|-----------|---------|

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Super Ultimate

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Component | State or local regulations |
|---------------------------|--|
| n-Heptane(142-82-5) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| oxydipropanol(25265-71-8) | U.S. - Pennsylvania - RTK (Right to Know) List |
| Ethyl acetate(141-78-6) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |
| Benzaldehyde(100-52-7) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 05/20/2021


Other information : None.

| Full text of H-statements | |
|---------------------------|--|
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Super Ultimate



Danger

Highly flammable liquid and vapor, Causes skin irritation, May cause drowsiness or dizziness, May be fatal if swallowed and enters airways

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, Keep container tightly closed, Ground/Bond container and receiving equipment, Use explosion-proof electrical, lighting, ventilating equipment, Use only non-sparking tools, Take precautionary measures against static discharge, Avoid breathing dust, fume, gas, mist, spray, vapors, Wash hands, forearms and face thoroughly after handling, Use only outdoors or in a well-ventilated area, Wear eye protection, face protection, protective clothing, protective gloves, If swallowed: Immediately call a poison center or doctor, Do NOT induce vomiting, If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower, If skin irritation occurs: Get medical advice/attention, Take off contaminated clothing and wash it before reuse, If inhaled: Remove person to fresh air and keep comfortable for breathing, Call a poison center or doctor if you feel unwell, Store in a well-ventilated place. Keep cool, Store locked up, Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Manufacturer

Distinctive Details Inc.
1253 Lower Elkton Rd.
Columbiana, OH 44408
1.800.711.7021

www.DistinctiveDetailsInc.com

Emergency number : 1-800-424-9300 (Chemtrec 24 Hr.
Emergency Line)

