

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 2025-05-23

Revision date: 2025-05-23 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Purple Dressing - VOC

Product code : 5722

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Exterior Rubber and Vinyl Dressing

1.3. Manufacturer

Manufacturer

Distinctive Details Inc. 1253 Lower Elkton Rd. Columbiana, OH 44408 T 1 800-711-7021

www.DistinctiveDetailsInc.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (Chemtrec 24 Hr. Emergency Line), Outside USA: 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Liq. 4 Asp. Tox. 1

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS)



Signal word (GHS) : Dange

Hazard statements (GHS) : Combustible liquid

May be fatal if swallowed and enters airways.

Precautionary statements (GHS) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center or doctor.

Do NOT induce vomiting.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with

local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Petroleum distillates, hydrotreated light	Petroleum distillates, hydrotreated light Hydrotreated light distillate / Kerosene, hydrotreated / Petroleum distillates, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 150-290°C.) / Odorless light petroleum hydrocarbons / Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, / Kerosene / c13-14 isoparaffin / Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9-14 Aliphaten) / Light Aliphatic Hydrocarbon / Odourless light petroleum hydrocarbons / Distillates (petroleum), hydro- treated light; Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150°C to 290°C (302°F to 554°F).] / Distillates, petroleum, hydrotreated light / Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	65 – 85

EN (English)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation

persists.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do not induce vomiting without

medical advice. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea,

vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns

and injuries.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool closed containers

exposed to fire with water spray.

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to

unnecessary and unprotected personnel. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Remove ignition sources. Absorb and/or contain spill with inert

material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal.II. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid

breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only non-sparking tools. Take action to

prevent static discharges. Ensure adequate ventilation.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-

ventilated place. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Purple Dressing - VOC

No additional information available

Petroleum distillates, hydrotreated light (64742-47-8)

No additional information available

Butanedioic acid, sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (577-11-7)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : No data available
Colour : No data available
Odour : No data available
Odour threshold : No data available

pH : 6 – 8

Melting point : No data available Freezing point : No data available Boiling point No data available Flash point No data available Relative evaporation rate (butylacetate=1) No data available Flammability Combustible Vapour pressure : No data available Relative vapour density at 20°C / 68 °F : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water No data available Auto-ignition temperature No data available Decomposition temperature No data available Viscosity, kinematic No data available Viscosity, dynamic No data available **Explosive limits** No data available Explosive properties No data available : No data available Oxidising properties

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sources of ignition. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg (Source: IUCLID)
LD50 dermal rabbit	> 2000 mg/kg (Source: NLM_CIP)
LC50 inhalation rat	> 5.2 mg/l/4h
Butanedioic acid, sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (577-11-7)	
LD50 oral rat	3080 mg/kg (Source: EPA_HPV)

Butanedioic acid, sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (577-11-7)	
LD50 oral rat	3080 mg/kg (Source: EPA_HPV)
LD50 dermal rabbit	> 10000 mg/kg (Source: CHEMVIEW)
ATE CA (oral)	3080 mg/kg bodyweight

Germ cell mutagenicity : Not classified.
Carcinogenicity : Not classified.
Reproductive toxicity : Not classified.

Petroleum	distillates,	hydrotreated	light	(6474	2-47-8)

NOAEL (animal/male, F0/P) ≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male STOT-single exposure : Not classified.

STOT-single exposure : Not classified.

STOT-repeated exposure : Not classified.

NOAEL (oral, rat, 90 days) 750 mg/kg bodyweight Animal: rat, Animal sex: female		750 mg/kg bodyweight Animal: rat, Animal sex: female
	THOMEE (ordi, rat, oo days)	700 mg/kg body weight / tillmai. rat, / tillmai oox. female
	NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal
		Toxicity: 90-Day Study)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Petroleum distillates, hydrotreated light (64742-47-8)	
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28- Day Study)
Butanedioic acid, sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (577-11-7)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 - Fish [1]	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: IUCLID)
LC50 - Fish [2]	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
Butanedioic acid, sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (577-11-7)	
LC50 - Fish [1]	20 – 40 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: EPA)
EC50 - Crustacea [1]	36 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	10.3 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

Purple Dressing - VOC	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Purple Dressing - VOC	
Bioaccumulative potential	Not established.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF - Fish [1]	61 – 159
Butanedioic acid, sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt (577-11-7)	
BCF - Fish [1]	3.47 – 3.78

12.4. Mobility in soil

No additional information available

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations

: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Recycle empty containers where allowed.

Additional information

: Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable Proper Shipping Name (TDG) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

TDG

Transport hazard class(es) (TDG) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 05/23/2025 Other information : None.

Full text of H-phra	Full text of H-phrases	
Asp. Tox. 1	Aspiration hazard Category 1	
Flam. Liq. 4	Flammable liquids Category 4	

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant


irritation.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively

high ambient temperatures before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire

conditions.



SDS HazCom 2012 - WHMIS 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.



Danger

Combustible liquid. May be fatal if swallowed and enters airways.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Manufacturer

Distinctive Details Inc.

1253 Lower Elkton Rd.

Columbiana, OH 44408

T 1 800-711-7021

www.DistinctiveDetailsInc.com

