



Distinctive Details
 1253 Lower Elkton Road
 Columbiana, OH 44408 USA
 1-800-711-7021

PRODUCT: Futura Foaming Spot Remover - 20oz.

Part # 90150

SECTION 01: IDENTIFICATION

Supplier..... Distinctive Details, Inc.
 Product Item Numbers..... 90150
 Product Identity..... Futura Foaming Spot Remover - 20 oz.
 24 hour emergency telephone number..... 1-800-424-9300 (Chemtrec 24 Hr. Emergency Line)
 Recommended Use..... Carpet spot remover .
 Chemical Family..... Mixture.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:
 Signal Word..... **WARNING.**
Hazard Classification:
 Physical Hazards..... Aerosols - Category 3. Gases Under Pressure - Liquefied Gas.
 Health Hazards..... Skin Irritation - Category 3. Eye Irritation - Category 2A.
 Environmental Hazards..... Not Classified.
 Hazard Statement..... H229:Pressurised container: May burst if heated (3). H280:Contains gas under pressure; may explode if heated (L). H316:Causes mild skin irritation. H319:Causes serious eye irritation.

Precautionary Statements:
 Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251:Do not pierce or burn, even after use. P280:Wear eye protection/face protection. P264:Wash hand thoroughly after handling.
 Response..... P332+P317:If skin irritation occurs: Get medical help. P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P317:If eye irritation persists: Get medical help.
 Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403:Store in a well ventilated place .
 Disposal..... None.
 Hazard(s) not otherwise classified (HNOC) Use only as directed.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Isobutane	75-28-5	5-10
Isopropyl alcohol	67-63-0	5-10
2-Butoxyethanol	111-76-2	1-5
Octoxynol	9036-19-5	1-5
Propane	74-98-6	0.5-1.5
Fragrance	Mix	0.1-1

SECTION 04: FIRST-AID MEASURES

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
 Skin Contact..... Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control centre or physician immediately.
 Eye Contact..... Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.
 Ingestion..... Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice.
 Most important symptoms/effects, acute .. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct and delayed contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.

PRODUCT: Futura Foaming Spot Remover - 20oz.

Part # 90150

SECTION 04: FIRST-AID MEASURES

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
 Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire.
 Specific Hazards Arising from the Chemical In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified Organic Compounds.
 Special Protective Equipment and Precautions for Firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
 General Fire Hazards..... Non Flammable aerosol, but contains flammable propellant.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).
 Methods and Materials for Containment and Cleaning Up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.
 Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.
 Conditions for Safe Storage including any Incompatibilities Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available	Not available
Isopropyl alcohol	400 ppm (980 mg/m3)	500 ppm (1,225 mg/m3)	400 ppm (980 mg/m3)	500 ppm (1,225 mg/m3)	400 ppm (980 mg/m3)	400 ppm (980 mg/m3)
2-Butoxyethanol	20 ppm	Not available	50 ppm	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available	Not available
Fragrance	Not established	Not established	Not established	Not established	Not established	Not established
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.					
Individual Protection Measures:						
Eye/Face Protection.....	Chemical splash goggles are recommended.					
Skin Protection.....	Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.					
Respiratory Protection.....	Use dust and mist respirator.					
Thermal Hazards.....	None Known.					
General Hygiene Considerations.....	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.					

PRODUCT: Futura Foaming Spot Remover - 20oz.

Part # 90150

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form.....	Aerosol.
Physical Appearance.....	Foam.
Odor.....	Fragrance.
Odor Threshold (ppm).....	N/A.
pH.....	Neutral.
Specific Gravity (Aerosol).....	0.900-1.000.
Vapour Pressure (psig).....	>30.
Auto Ignition Temperature (°C).....	460°C (860°F). (Propellant).
Evaporation Rate (n-Butyl Acetate = 1).....	Not available.
Flash Point (°C), Method.....	-82.8. Closed cup. (Propellant).
Boiling Point (°C).....	Not available.
Melting/Freezing Point (°C).....	N/A.
VOC Content.....	NMT 15.
Solubility in water.....	Soluble.
Lower Flammable Limit (% Vol).....	1.8. (Isobutane).
Upper Flammable Limit (% Vol).....	8.8. (Isobutane).
Note.....	NMT = Not More Than.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Product not reactive under normal conditions of use.
Chemical Stability.....	Material is stable under normal conditions.
Possibility of Hazardous Reactions.....	Will not occur.
Conditions to Avoid.....	Avoid sources of heat and flame, and electrostatic charge.
Incompatible Materials.....	Keep away from heat. Strong oxidizing agents.
Hazardous Decomposition Products.....	See Section 05.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Isobutane	658 mg/L (Rat - 4 hrs)	Not available
Isopropyl alcohol	73 mg/L (Rat - 4hrs)	3,636 mg/kg (Oral - Rat); 4,059 mg/kg (Dermal - Rabbit)
2-Butoxyethanol	450 ppm (Rat - 4 hrs)	470 mg/kg (Oral - Rat)
Propane	658 mg/L (Rat - 4 hrs)	Not available
Fragrance	No data	No data
Information on Likely Routes of Exposure:		
Routes of entry - Inhalation.....	Yes.	
Routes of entry - Skin & Eye.....	Yes.	
Routes of entry - Ingestion.....	Yes.	
Routes of entry - Skin Absorption.....	No.	
Symptoms Related to the Physical,	Irritant effects.	
Chemical and Toxicological Characteristics		
Acute Toxicity.....	No known significant effects.	
Skin Corrosion/Irritation.....	Causes mild skin irritation. Prolonged contact may be more irritating.	
Serious Eye Damage/Eye Irritation.....	Causes serious eye irritation.	
Respiratory or Skin Sensitization.....	Not classified.	
Germ Cell Mutagenicity.....	No information is available, and no adverse effects are expected.	
Carcinogenicity.....	Not Classifiable as a Human Carcinogen.	
Reproductive Toxicity.....	No information is available, and no adverse effects are expected.	
STOT - Single Exposure.....	Not classified.	
STOT - Repeated Exposure.....	Not classified.	
Aspiration Hazard.....	Not classified.	
Chronic Effects.....	No information is available, and no adverse effects are expected.	

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity.....	May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. This product contains the following substance which may also be hazardous for the environment: Isopropanol (CAS#: 67-63-0): Toxicity to fish: LC50 9,640 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 5,102 mg/L, 96 hrs;
Persistence and degradability	Toxicity to algae: EL50 >2,000 mg/L, 72 hrs.
Bioaccumulation Potential.....	The product itself has not been tested.
Mobility in Soil.....	The product itself has not been tested.
Other Adverse Effects.....	None Known.

PRODUCT: Futura Foaming Spot Remover - 20oz.

Part # 90150

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.2, Ltd. qty.
 DOT (US-Road)..... UN1950, AEROSOLS, Class 2.2, Ltd. qty., Consumer Commodity, ORM-D.
 IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.2, Ltd. qty.
 IATA (International- Air)..... UN1950, AEROSOLS, Class 2.2, Ltd. qty.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:
 Canadian Environmental Protection Act ... All ingredients listed appear on the Domestic Substances List (DSL).
 (CEPA)
 US Regulations
 TSCA Inventory Status..... All components are either listed or exempt from the TSCA.
 OSHA..... This product is considered hazardous under the Federal OSHA hazard communication standard.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by Regulatory Affairs
 Latest Revision 2023-06-20